

BoneDryTM XT

2034-C Van Buren Ave. • Indian Trail, NC 28079 • Phone: 704.334.8222

BoneDry™ XT is a commercial grade waterproofing membrane based on polymer modified asphalt emulsion. BoneDry™ XT is used as a below-grade exterior waterproofing compound and exhibits excellent strength, adhesion, and flexibility. BoneDry™ XT is a premium grade waterproofing compound used in commercial building construction and can be used for all other types of below-grade waterproofing as well.

BoneDryTM XT is spray applied and can instantly build virtually any thickness¹ your job demands. Instant thickness means you can install the remainder of your waterproofing system immediately after the product has been sprayed – no additional trips to complete waterproofing because your membrane isn't cure.

Technical Data

Color		Black/Brown
Solids		63% ± 2%
Thickness		40-60 mil dry
Tensile Strenth	ASTM D-412	87 psi
Elongation	ASTM D-412	1800%
MVT	ASTM E-96	0.19 gr/hr*sq.ft
Adhesion to Concrete	ASTM C-834	Exceeds
Shore Hardness	ASTM C-836	75
Crack Bridging	ASTM C-836	Exceeds
Low Temp Flexibility	ASTM C-836	No Cracking
Perm Rating	ASTM C-836	0.38 perms
		/ 400

For more application information visit www.drydogbarriers.com or email us info@drydogbarriers.com

Applications

- Masonry Foundations
- Poured Foundations
- Pre-Cast Foundations
- Horizontal Waterproofing
- Planters
- Retaining Walls
- Cavity Wall Air Barrier

¹ To obtain recommended thickness this product must be used with BoneDry™ Accelerator.



BoneDry $^{\text{IM}}$ XT waterproofing membrane shown with available12" DrainMax $^{\text{IM}}$ foundation strip drain to make the BD1000 Waterproofing System